

AMENDMENTS TO THE CLAIMS

This listing of claims will replace all prior versions and listings of claims in the application.

LISTING OF CLAIMS

Claims 1-17 (canceled)

18. (new) A cuff apparatus for measuring blood pressure, comprising:
- a chassis;
 - a hollow cylindrical airbag having inner and outer walls, and received in the chassis, for suppressing a flow of blood of a human body by the inner wall when compressed air is introduced into the airbag;
 - a plurality of cushions provided in the airbag, for causing the airbag to remain in an inflated state before compressed air is introduced into the airbag; and
 - first and second microphones which are arranged in the airbag to oppose each other, so that the first microphone detects Korotkoff sounds at a right upper arm of the human body near arteries thereof when the right upper arm is inserted through and covered with the hollow cylindrical airbag and the compressed air is introduced into the airbag, and the second microphone detects Korotkoff sounds at a left upper arm of the human body near arteries thereof when the left upper arm is inserted through and covered with the hollow cylindrical airbag and the compressed air is introduced into the airbag.

19. (new) A cuff apparatus according to claim 18, wherein each of the cushions is attached to an inside of the outer wall of the airbag at one side, and has an uneven wall on an opposite side.

20. (new) A cuff apparatus according to claim 18, wherein the cushions are fixed on an inside of the outer wall of the airbag, and spaced apart from one another in a circumferential direction.

21. (new) A cuff apparatus according to claim 18, wherein said first and second microphones are attached to portions of an outside of the inner wall, corresponding to the cushions.

22. (new) A cuff apparatus according to claim 18, wherein the cushions include first, second and third cushions fixed on an inner side of the outer wall, the second and third cushions being arranged symmetrically with respect to the first cushion in a circumferential direction of the cylindrical airbag;

said first and second microphones are attached to portions of an outside of the inner wall, corresponding to the second and third cushions.

23. (new) A cuff apparatus according to claim 18, which further comprises an elastic band-shaped member attached to an inner side of the outer wall.

24. (new) A cuff apparatus according to claim 23, wherein the elastic band-shaped member is arranged on an inlet side of the airbag through which the upper

arm is inserted into the airbag, and extended in a circumferential direction of the cylindrical airbag.

25. (new) A cuff apparatus according to claim 18, wherein the cylindrical airbag is formed by bending an elongated rectangular airbag strip in a cylindrical shape, and overlapping opposite end portions of the airbag strip in a longitudinal direction thereof.

26. (new) A cuff apparatus according to claim 25, which further comprises an auxiliary cushion attached to an inner side of the outer wall near the overlapping opposite end portions of the airbag strip.

27. (new) A cuff apparatus according to claim 26, wherein the auxiliary cushion has a thickness gradually increasing in an insert direction of the upper arm.

28. (new) A cuff apparatus according to claim 18, which further comprises a pair of pockets attached to an inner side of the inner wall of the airbag, each of the microphones being inserted in each one of the pockets.

29. (new) A cuff apparatus according to claim 28, which further comprises a cable holder attached to the airbag between the pockets, and a cable connecting the microphones and supported by the cable holder.

30. (new) A cuff apparatus according to claim 18, in which a plurality of fasteners are provided on an outer circumferential surface of the airbag, each having a flange shaped like a mushroom cap, and the chassis has engagement holes in which the flanges of the fasteners are fitted, thereby fastening the airbag to the chassis.

31. (new) A cuff apparatus according to claim 30, wherein each of the engagement holes is shaped like a gourd, and is formed by a large hole and a small hole connected to each other, and each of the flanges shaped like a mushroom cap is moved from the large hole to the small hole to be set in the engagement hole.

32. (new) A cuff apparatus according to claim 30, wherein each of the fasteners has a conduit therein for supplying and discharging compressed air into and from the airbag.

33. (new) A cuff apparatus according to claim 30, wherein each of the fasteners has a conduit therein for detecting pressure of the compressed air in the airbag.

34. (new) A cuff apparatus according to claim 32, wherein a filter is provided in the conduit for preventing chips of the cushions from entering the conduit.

35. (new) A cuff apparatus according to claim 18, wherein an inner circumferential surface of the hollow cylindrical airbag received in the chassis is covered with a cloth cover made of flexible fibers.

36. (new) A cuff apparatus according to claim 35, wherein the cloth cover is formed in the shape of a hollow cylinder and has an elastic ring at each end, and elastic rings are fitted in recesses formed in the housing of a sphygmomanometer, whereby the cloth cover is removably secured to the housing.